



**LAVAT**  
Laboratory and Vacuum Technique

Tovární  
ulice 35  
281 03      [www.lavat.cz](http://www.lavat.cz)  
Radim u      [info@lavat.cz](mailto:info@lavat.cz)  
Kolína      321 792 312  
Česká  
Republika

## PVC hose with embedded spring KF 40/ 1000

Zák. číslo: 2934 76 0000

PVC hose is structural component designed for flexible connections in vacuum installations. Flexible robust hose is reinforced with embedded steel coil and hose cover is from transparent PVC. Working temperature is from - 5 to 65 °C. The minimum bending radius is applicable for a temperature of 20 °C. The bending radii increase at larger temperatures up to factor 1,5 at 50 °C.

### Technické údaje

|                   |                                                   |
|-------------------|---------------------------------------------------|
| Inner tube        | PVC, transparent                                  |
| Casing            | steel coil                                        |
| Surface of hose   | Smooth inner and outer walls                      |
| DN                | 40                                                |
| Bending radius    | 110 mm                                            |
| Dimensions (L)    | 1000 mm                                           |
| Pressure range    | 1 x 10 <sup>-4</sup> hPa to 500 hPa over pressure |
| Temperature range | -5 to 65 °C                                       |

### Fotogalerie

